

→ IDEAL 4850-95

GUILLOTINE WITH AUTOMATIC CLAMP


475 mm cutting length | electro-mechanical blade and clamp drive | optical cutting line | spindle guided backgauge with hand crank | measuring scale (mm/inches), located on front table | two side lays each on front and rear tables | high-quality blade made from "Solingen steel" | solid steel blade carrier and adjustable blade guides | blade depth adjustment from the outside of the machine | easy blade change from the front of the machine without removing covers | automatic clamping system, guided on both sides for evenly distributed clamping pressure (clamp can be lowered or raised independently from blade) | comprehensive "SCS" safety package as described on pages 8/9 | adjustable backgauge with narrow separations and plastic gliders | solid all-metal construction | complete with stand and storage shelf

Power supply: 230 V / 50 Hz / 1~¹, Motor performance (input capacity): blade drive 1.1 kW, clamp drive 0.32 kW, Dimensions (H x W x D): 1230 x 755 x 970 mm, Weight: 209 kg, Colour: pearl grey.

¹ other voltages available



SAFETY GUARD



The electronically secured front safety guard swings out of the way easily and allows safe and convenient cutting.

PUSH BUTTON CONTROL



Push buttons allow the automatic clamp to be moved up and down independently of blade.

MEASURING SCALE



The precise measuring scale (mm/inches) for the backgauge positioning can be read easily and is located on the front table.

→ IDEAL 4850-95

Cutting length	475 mm
Cutting height	80 mm
Narrow cut	30 mm
Table depth	458 mm
Power supply	230 V / 50 Hz ¹