

# → IDEAL 4850-95 EP

## GUILLOTINE WITH AUTOMATIC CLAMP AND PROGRAMMABLE »EP« POWER BACKGAUGE

Basic features same as for model IDEAL 4850-95, but equipped with: power backgauge with "EP" backgauge control module | digital display for measurement readout in cm or inches (display accurate to 1/10 mm or 1/100 inch) | 10-button key pad for presetting of measurement | memory key for repeat cuts | programmable "EP" backgauge control module for 9 programs with 9 steps in each program (up to 9 repeat cuts can be integrated into a program as one single program step) | setting of program steps via "Start" button | "SET" function key for reference measurement | programmable EJECT function – for pushing out the paper | two programmable keys for quick setting of frequently needed measurements | electronic hand wheel for manual backgauge positioning with infinitely variable speed control (from very slow to very fast) | self-diagnosis system with error indication on display

Power supply: 230 V / 50 Hz / 1~<sup>1</sup>, Motor performance (input capacity): blade drive 1.1 kW, clamp drive 0.32 kW, backgauge drive 0.1 kW, Dimensions (H x W x D): 1230 x 755 x 970 mm, Weight: 215 kg, Colour: pearl grey.

<sup>1</sup> other voltages available



### “EP” BACKGAUGE CONTROL




Fully programmable backgauge control module with digital measurement readout, 10 push button key pad, and memory key for repeat cuts.

### ELECTRONIC HAND WHEEL



Electronic hand wheel for manual backgauge positioning with infinitely variable speed control (from very slow to very fast).

### OPTICAL CUTTING LINE



The optical cutting line shows where the cut will be performed and helps to align cutting marks precisely for accurate cuts.

### → IDEAL 4850-95 EP

Cutting length	475 mm
Cutting height	80 mm
Narrow cut	35 mm
Table depth	450 mm
Power supply	230 V / 50 Hz <sup>1</sup>