

→ IDEAL 6550-95 EP

PROGRAMMABLE GUILLOTINE

650 mm cutting length | electro-mechanical blade drive | automatic clamping system (clamp can be lowered or raised independently from blade) | power backgauge with fully programmable "EP" backgauge control module and digital measurement readout | digital display for measurement readout in cm or inches (display accurate to 1/10 mm or 1/100 inch) | 10-button key pad for presetting of measurement | memory key for repeat cuts | programmable "EP" backgauge control module for 9 programs with 9 steps in each program (up to 9 repeat cuts can be integrated into a program as one single program step) | setting of program steps via "Start" button | "SET" function key for reference measurement | programmable EJECT function - for pushing out the paper | two programmable keys for quick setting of frequently needed measurements | self-diagnosis system with error indication on display | electronic hand wheel for manual backgauge positioning with infinitely variable speed control (from very slow to very fast) | optical cutting line | clamp guided on both sides for evenly distributed clamping pressure | spindle guided backgauge for precise positioning | adjustable backgauge with narrow separations and plastic gliders | two side lays each on front and rear tables | solid steel blade carrier and adjustable blade guides | comprehensive IDEAL safety package as described on pages 8/9 | complete with stand and storage shelf

Power supply: 230 V / 50 Hz / 1~¹, Motor performance (input capacity): blade drive 1.1 kW, clamp drive 0.32 kW, backgauge drive 0.1 kW, Dimensions (H x W x D): 1220 x 995 x 1260 mm, Weight: 304 kg, Colour: pearl grey.

¹ other voltages available



"EP" BACKGAUGE CONTROL



9 programs with 9 steps in each program can be stored in the "EP" backgauge control module. A memory key is available for repeat cuts.

ELECTRONIC HAND WHEEL



The electronic hand wheel with infinitely variable speed (from very slow to very fast) allows manual setting of the backgauge.

OPTICAL CUTTING LINE



The optical cutting line facilitates alignment of cutting marks and guarantees precise cuts.

→ IDEAL 6550-95 EP

Cutting length	650 mm
Cutting height	80 mm
Narrow cut	25 mm
Table depth	610 mm
Power supply	230 V / 50 Hz ¹