

WIDE FORMAT LAMINATOR



RSL-382S / 2702S

1. Sales Point

- All in one digital finisher at an affordable price
- Mounting up to 6mm/0.24"
- Digital temperature and speed control
- Chain driven synchronized take up device
- Single sided lamination possible(OPP film)
- De-Curling Device
- Large film roll capacity(up to 200mm / 7.9" diameter)
- Hot & Cold Laminating



2. Specification

Description	RSL-2702S	RSL-382S
Power supply	AC 100, 200, 220~240V 50/60Hz 120V 60Hz	
Power consumption	1500W	1200W
Max. laminating width	685mm / 27"	380mm / 14.9"
Film thickness	25~250 mic / 1~10mil / Opp film 32mic	
Paper thickness	Single	200~250g
	Double	80~250g
Max. laminating speed	4.5m/min	
Ready time	10min	
Heating method	Hot roller	
Driving motor	DC geared	
Max. Temperature control	150°C / 302°F	
Speed control	9 settings	
Transport type	4 Rollers	
Film core size	Auto grip (2", 3")	Auto grip (2", 3"); Core 1"
Cooling system	2 AC Fan	No
Cross cutter	Yes	
Hot lamination	Single	Yes
	Double	Yes
Cold lamination	Yes	
Mounting thickness	6mm / 0.24"	
Take up system	Chain link to main motor	
Reverse	Yes	
Unit dimensions (w x d x h)	970×540×470 (mm)	640×550×470 (mm)
	38"×21.5"×18.5"	25"×22"×18.5"

ROYAL SOVEREIGN QINGDAO INC.